

# Type 2 X/Y Tracking Antenna

## KEY FEATURES

- X/Y axis configuration
- No 'cone of silence' at zenith
- Ideal for tracking LEO, MEO and GEO spacecraft
- Ethernet (TCP/IP) antenna control and monitoring
- Bespoke software control
- Low power consumption
- High reliability

## AVAILABLE OPTIONS

- Dual frequency / polarization
- High performance LNAs
- Full RF chain:
  - Frequency converters
  - Spectrum analysers
  - RF switching
  - Demodulators/modems
  - Uplink amplifiers
- Anti-icing
- Webcams
- Vehicle mountable
- Radomes
- Installation services
- Civil engineering



## MECHANICAL

Antenna Mount	Type 2 X/Y
Aperture Size	3.0m—3.6m (Outdoor System) 3.0m—4.2m (In-Radome System)
Pointing Accuracy	<0.1°
Position Step Resolution	0.00004°
Acceleration	10°/s <sup>2</sup> max
Velocity	4°/s typical
Degrees of Freedom	2 (X and Y)
Axis Travel	Full hemispheric coverage
Horizon limits	-2° typical

## CONTROL SYSTEM

Interface	Ethernet
Power	110/240Vac, 1ph, 13A

## RF

Frequency Range	L, S, X, C, Ku and Ka Band
Polarisation	LHCP and/or RHCP
Feed Configuration	Prime Focus
Performance	Please enquire

## ENVIRONMENTAL

Wind Speed	80km/h wind (Operational) <sup>(1)</sup> 200km/h wind (Survival)
Temperature	-40°C—+50°C (Operational) <sup>(1)</sup> -45°C—+60°C (Survival)
Humidity	100% Relative Humidity
Driving Rain	Upto 10cm/hr

## CGC SPACE

Unit E Grovebell Industrial Estate  
Wrecclesham Road  
Farnham  
Surrey  
GU10 4PL  
United Kingdom  
Phone: +44 (0) 1252 724 274  
Fax: +44 (0) 1252 722 624  
E-mail: info@cgc-space.com



(1) Optional measures (heaters, radomes, HVACs) can be taken to improve operational environmental limits